

## **PRODUCT DATA SHEET F-LON® 7010 Series**

**F-LON® 7010** is an advanced **chemical resistant** coating.

**F-LON® 7010** is a high purity Fluoropolymer coating based on a unique alternating, copolymer offering excellent protection against chemical attack and ingress.

### **F-LON® 7010 Series**

<b>Recommended Dry Film Thickness</b>	0.2 to 1.5mm
<b>Substrates</b>	Most metallic substrates.
<b>Pre-treatment</b>	Degrease followed by sandblasting.
<b>Application method</b>	Hand spray or automatic spray line.
<b>Curing schedule</b>	270°C
<b>Operating Temperature</b>	-40 to + 150°C
<b>Colours available</b>	Green
<b>Typical applications</b>	Pharmaceutical, Fine Chemicals and Semiconductor process plant demanding high purity and low vapour permeation.
<b>Other properties</b>	Chemical resistance Abrasion resistance Corrosion resistance

*This product data sheet is based on the best information currently available and is offered to users in good faith but without offering or implying a warranty that such information is correct or has not been amended. Nor may it be assumed that patents, copyrights or design registrations concerning systems referred to herein may be ignored.*

F-LON® is a registered trademark of Fluorocarbon, Caxton Hill, Hertford, Herts, SG13 7NL

Issue 1